



ETICS internal on masonry

Thermal insulation composite system for internal walls in wood fiber Internal and cement bonded particle boards on masonry

The complete system for the construction of high-performance internal walls and counter-walls. The ETICS internal on masonry solution has excellent characteristics of mechanical resistance and thermal insulation, and guarantees maximum comfort and maximum durability over time. Complete system: panels, skimming products, fixing products and accessories

STRATIGRAPHY	DESCRIPTION	QUANTITY	PRICE	TOTAL
1 Wall	Masonry, wood, or X-Lam wall			
2 Wood frame	Wood frame structure			
3 Wood fiber panels FiberTherm Internal160	<p>FiberTherm Internal wood fiber insulation panels are ideal even in limited space situations. Available with tongue&groove profile or with sharp and flat edge. Density equal to 160 Kg / m³.</p> <p>FiberTherm Internal wood fiber insulation panels spread the steam and allow the capillary transport of steam. FiberTherm Internal protects the living area from molds as it provides an optimal moisture balance to create an environment in which mold is not formed. Available in the following sizes: 1350x600 mm and 1200x380 mm. Available in thicknesses: 20, 40, 60 mm.</p> <p>The wood used in the processing of the panels comes from forests controlled by FSC reforestation cycles.</p>			
4 Cement bonded particle boards BetonWood N	<p>The BetonWood N cement bonded particle boards, with high density (1350 Kg/m³), made of Portland-type cement conglomerate and debarked Pine wood fiber. These panels have the following termo-dynamics characteristics: thermal conductivity coefficient $\lambda=0,26$ W/mK, specific heat $c=1,88$ KJ/Kg K, coefficient of resistance to vapor penetration $\mu=22,6$ and reaction to fire class A2-fl-s1, according to the standard EN 13501-1.</p> <p>Available in the following sizes: 870x515 mm, 1012x515 mm, 1025x515 mm, 1200x500 mm, 1220x500 mm. Thicknesses from 18 to 22 mm. Available with stepped, tongue&groove and sharp edges.</p>			
5 Screws NF57	The screw has a special anti-corrosion coating that guarantees a 1,000-hour salt spray resistance. Under-head with very sharp self-sinking fins for a perfect housing of the head flush with the slab. Spoon tip (spoon) with very high perforation capacity.			
6 Skimming layer Beton AR1	<p>Monocomponent cementitious mortar for bonding and smoothing of thermal insulation panels and BetonTherm "reinforced thermal insulation composite systems".</p> <ul style="list-style-type: none"> • 1,3 - 1,5kg/m² per mm of skimming layer thickness (recommended: approx. 4 mm within 2 hands). Application: spatula 			
7 Net BetonGlass 360	The net has density 360 g/m ³ and complies with the ETAG004 Guideline for ETICS (External Thermal Insulation Composite System), as certified by IFBT GmbH-MF-PA Leipzig GmbH. It is suitable for internal and external armored thermal insulation (suitable for any type of BetonTherm product). 50 m ² rolls.			
8 Skimming layer Beton AR1	<p>Monocomponent cementitious mortar for bonding and smoothing of thermal insulation panels and BetonTherm "reinforced thermal insulation composite systems".</p> <ul style="list-style-type: none"> • 1,3 - 1,5kg/m² per mm of skimming layer thickness (recommended: approx. 4 mm within 2 hands). Application: spatula 			



The functionality of the system will be covered by a BetonWood guarantee for the characteristics of air tightness, water proofing and isolation of the technological package. The warranty will be documented with the appropriate Certificate and Certificate of Assurance that will be delivered at the end of the work to the DD.LL. from the same layer. The forms are available on the BetonWood website as well as the technical indications, the application matrix and the exclusion clauses.

TOTAL AMOUNT